

FTTH Drop Cable Type Fiber Optic Splice & Splitter Closure

Description

FTTH Drop Cable Type Fiber Optic Splice & Splitter Closure features with ruggedness, which is tested under harsh conditions and stand up to even the most severe conditions of moisture, vibration and extreme temperatures. Humanized design helps user get better experience.

Features

- Dis-mountable adaptor panel
- Support midspan termination
- Easy operation and installation
- Rotatable and dis-mountable splice tray for easy splicing
- Protection Level: IP68



Part Number	Description
FB WL 16	16 - port

Applications

- Wall mounting & pole mounting installation
- 2*3mm Indoor FTTH Drop Cable and Outdoor Figure 8 FTTH Drop Cable



Part Number	Description
FB WL 24-2	24 - port

Specification

Model	FB WL 24	FB WL 16	FB WL 24-2
Adapter	24pcs of SC	24 pcs of SC	24pcs of SC
Cable Ports	1 uncut port	1 uncut port 2 round ports	1 uncut port 2 round ports
Applicable Cable Diameter	10~17.5mm	10~17.5mm 8~17.5mm	10~17.5mm 8~17.5mm
Drop Cable Ports	24 ports	16 ports	24 ports
Applicable Cable Diameter	2*3mm FTTH Drop Cable, 2*5mm Figure 8 FTTH Drop Cable		
Dimension	385*245*130mm	385*245*130mm	385*245*155mm
Material	modified polymer plastic		
Sealing Structure	mechanical sealing		
Color	black		
Maximum Splicing Capacity	48 fibers (4 trays, 12 fibers/tray)		
Applicable Splitter	1pc of 1*16 PLC Splitter or 2pcs of 1*8 PLC Splitters		
Sealing	IP67		
Impact Test	Ik10		
Pull Force	100N		
Midspan Entry	yes		
Storage (Tube/Micro Cable)	yes		
Net Weight	4kg		
Gross Weight	5kg		
Packing	540*410*375mm (4pcs per carton)		